

ECOBULK

CC/FC BREATHER

The new ventilation system for our SCHÜTZ CLEANCERT and SCHÜTZ FOODCERT variants.



The new CC/FC BREATHER offers maximum convenience and protection when discharging filling goods and simplifies the legally-compliant return of empty packaging:

- To avoid negative pressure in the container and deformation of the inner bottle during product removal via the outlet valve, ventilation is required to equalise the pressure
- Instead of removing the entire screw cap or bung plug, the CC/FC BREATHER opens venting paths in the component by turning the screw upwards – fast and without tools
- After emptying, the container can simply be closed – contamination risks are minimised even during the entire emptying process and the packaging is returned safely and within the framework of legal requirements


In case of technical concerns or questions: tcs@schuetz.net

SCHÜTZ
PACKAGING SYSTEMS

www.schuetz.net

Ventilation when emptying filling goods

1. Remove the bung seal on the screw cap



Seal cap

or



AUTOMATIC LOCK

2. Open the venting paths in the plug underneath by turning the screw up as far as the stop



3. Close the screw cap after emptying:

Remaining product is protected from contamination

After complete emptying, the closed state meets the requirements for transport for returning IBCs



Versions available



Without permanent vent



With permanent vent and splash guard (D15 and D38)

