

# ECOBULK HX

Highest purity and efficiency for high-viscosity filling goods.



- Specially designed for filling goods such as coatings, adhesives, resins, viscous foods
- Ideal for the most demanding applications, e.g. automotive coatings
- Material of components that come into contact with the filling good free of silicones
- Closed, sturdy cushion to provide the best possible support for the inner bottle
- Zero administration and free collection with the SCHÜTZ TICKET SERVICE
- Residual drainability < 0.3 litres
- Optimised for use with stirring systems down to 50 litres residual content

In case of technical concerns or questions: [tcs@schuetz.net](mailto:tcs@schuetz.net)



[www.schuetz.net](http://www.schuetz.net)

## Material

### Inner bottle

Inner and intermediate layer: high-molecular, high-density polyethylene (HDPE)  
Antistatic outer layer (optional)  
Additional UV and light protection of the filling product (optional)

### Outer container

Welded tubular steel grid, galvanized  
**Bottom plate**  
Made of steel to provide stability and to facilitate minimum residual contents from the inner container  
Acid protector component included

## Pallets (4-way entry)



plastic skid

## Certifications

### UN 31 HA1/Y (optional)

Maximum density 1.9 g/cm<sup>3</sup>

### Suitable for use in ex-zones 1 and 2 (optional)

Tested for electrostatic safety

### SCHÜTZ FOODCERT (optional)

System certification for food (contains materials that are FDA compliant)

### SCHÜTZ CLEANCERT (optional)

For highest safety and technical cleanliness

## Capacity

### HX 1000

1,000 litres (275 gal)

## Filling opening

DN 225 with screw cap

## Outlet valves

(Earthed) integrated butterfly valve DN 50

(Earthed) screwable butterfly valve DN 50, DN 80

## Dimensions (mm)

### HX 1000

1,200 x 1,000 x 1,350 (L x W x H)

## Weight

### HX 1000

88 kg with plastic skid pallet

## Dynamic load

Filled ECOBULK according to the specific weight of the filling goods

## Static load

Max. 3-high

