

ECOBULK HX

Highest purity and efficiency for high-viscosity filling goods.



- Specially designed for filling goods such as coatings, adhesives, resins, viscous foods
- Ideal for the most demanding applications, e.g. automotive coatings
- Material of components that come into contact with the filling good free of silicones
- Closed, sturdy cushion to provide the best possible support for the inner bottle
- Zero administration and free collection with the SCHÜTZ TICKET SERVICE
- Residual drainability < 0.3 litres
- Optimised for use with stirring systems down to 50 litres residual content

In case of technical concerns or questions: tcs@schuetz.net

SCHÜTZ
PACKAGING SYSTEMS

www.schuetz.net

Material

Inner bottle

Inner and intermediate layer: high-molecular, high-density polyethylene (HDPE)
Antistatic outer layer (optional)
Additional UV and light protection of the filling product (optional)

Outer container

Welded tubular steel grid, galvanized
Bottom plate
Made of steel to provide stability and to facilitate minimum residual contents from the inner container
Acid protector component included

Pallets (4-way entry)



steel frame

steel skid

plastic skid

Certifications

UN 31 HA1/Y (optional)

Maximum density 1.9 g/cm³

Suitable for use in ex-zones 1 and 2 (optional)

Tested for electrostatic safety

SCHÜTZ FOODCERT (optional)

System certification for food (contains materials that are FDA compliant)

SCHÜTZ CLEANCERT (optional)

For highest safety and technical cleanliness

Capacity

HX 1000

1,000 litres (275 gal)

Filling opening

DN 225 with screw cap

Outlet valves

(Earthed) integrated butterfly valve DN 50, DN 80

Dimensions (mm)

HX 1000

1,200 x 1,000 x 1,350 (L x W x H)

Weight

HX 1000

88 kg with plastic skid pallet

Dynamic load

Filled ECOBULK according to the specific weight of the filling goods

Static load

Max. 3-high

