

ECOBULK LX COMPOSITE

With plastic-composite pallet.



- Improved handling properties
- Improved stability and robustness
- Significantly reduced variation of tara weight
- Best suitability for conveyor belts and shipping in ISO-containers
- Weatherproof and mildew-proof
- Easy and efficient stacking for best storage room utilisation
- Significant reduction of active staining by abrasion, splints or debris
- Improved reuse capability
- Environmentally friendly

In case of technical concerns or questions: tcs@schuetz.net

SCHÜTZ
PACKAGING SYSTEMS

www.schuetz.net

Material

Inner bottle

Extrusion blow-moulded HDPE
SMP protective barrier (optional)

Outer container

Welded tubular steel grid, galvanized

Pallets (4-way entry)



Plastic-composite

Certifications

UN 31 HA1/Y (optional)
Maximum density 1.6 g/cm³

Capacity

LX 1000
1,000 litres (275 gal)

Filling opening

DN 150 with screw cap
DN 225 with screw cap

Outlet valves

Integrated butterfly valve DN 50

Dimensions (mm)

LX 1000
1,200 x 1,000 x 1,160 (L x W x H)

Weight

LX 1000
61 kg with plastic-composite pallet

Dynamic load

Filled ECOBULK according to the specific weight of the filling goods

Static load

Max. 3-high

