

# ECOBULK LX COMPOSITE

With plastic-composite pallet.



- Improved properties compared to the standard wooden pallet: handling, stability and robustness
- Significantly reduced variation of tara weight
- Best suitability for conveyor belts and shipping in ISO-containers
- Weatherproof and mildew-proof
- Easy and efficient stacking for best storage room utilisation
- Significant reduction of active staining by abrasion, splints or debris
- Improved reuse capability
- Environmentally friendly

In case of technical concerns or questions: [tcs@schuetz.net](mailto:tcs@schuetz.net)



[www.schuetz.net](http://www.schuetz.net)

## Material

### Inner bottle

Extrusion blow-moulded HDPE  
SMP protective barrier (optional)  
UV and light protection (optional)

### Outer container

Welded tubular steel grid, galvanized

## Pallets (4-way entry)



Plastic-composite

## Certifications

UN 31 HA1/Y (optional)  
Maximum density 1.6 g/cm<sup>3</sup>

## Capacity

**LX 1000**  
1,000 litres (275 gal)

## Filling opening

DN 150 with screw cap  
DN 225 with screw cap

## Outlet valves

Integrated butterfly valve DN 50, DN 80

## Dimensions (mm)

**LX 1000**  
1,200 x 1,000 x 1,160 (L x W x H)

## Weight

**LX 1000**  
61 kg with plastic-composite pallet

## Dynamic load

Filled ECOBULK according to the specific weight of the filling goods

## Static load

Max. 3-high

