

ECOBULK MX

Perfect for transport
and storage.



- Approved for filling products of a maximum density of 1.9
- Perfectly suited for high bay warehousing
- Can be stacked up to 4-high
- Reinforced, warp resistant tubular steel grid jacket
- Additional corner guards to protect the inner container
- Available in a variety of equipment packages

In case of technical concerns or questions: tcs@schuetz.net

SCHÜTZ
PACKAGING SYSTEMS

www.schuetz.net

Material

Inner bottle

Extrusion blow-moulded HDPE
SMP protective barrier (optional)
Additional UV and light protection of the filling product (optional)

Outer container

Welded tubular steel grid, galvanized

Bottom plate

To provide stability and to facilitate minimum residual contents from the inner container

Pallets (4-way entry)



Certifications

UN 31 HA1/Y (optional)
Maximum density 1.9 g/cm³
SCHÜTZ FOODCERT (optional)
System certification for food (contains materials that are FDA compliant)

Capacity

MX 640
640 litres (170 gal)
MX 820
820 litres (220 gal)
MX 1000
1,000 litres (275 gal)
MX 1250
1,250 litres (330 gal)

Filling opening

DN 150 with screw cap
DN 225 with screw cap
DN 400 with clamp-ring lid (only for MX 1000)

Outlet valves

Integrated butterfly valve DN 50, DN 80
Screwable butterfly valve DN 50, DN 150
Screwable ball valve DN 50

Dimensions (mm)


MX 640
1,200 x 800 x 1,000 (L x W x H)
MX 820
1,200 x 1,000 x 1,000 (L x W x H)
MX 1000
1,200 x 1,000 x 1,160 (L x W x H)
MX 1250
1,200 x 1,000 x 1,350 (L x W x H)

Weight

MX 640
48 kg with plastic skid pallet
MX 820
51 kg with steel pallet
54 kg with plastic skid pallet
MX 1000
56 kg with steel pallet
59 kg with plastic skid
59 kg with full-plastic pallet
MX 1250
65 kg with steel pallet
68 kg with plastic skid pallet

Dynamic load

Filled ECOBULK according to the specific weight of the filling goods



Static load

Max. 4-high

