

ECOBULK

MX-EX

WITH EX-APPROVED
PLASTIC-SKID PALLET

SCHÜTZ plastic pallets –
now available for ex-zones!



- The IBC is earthed by metal contact plates in the outer runners
- Giving full ex-protection even when the IBCs are stacked
- Environmentally friendly through the use of high-quality recyclate material from our reconditioning service
- Exceptionally stable and impact resistant
- Very good resistance to chemicals
- Hygienic and corrosion resistant
- Pallet has excellent liftability

In case of technical concerns or questions: tcs@schuetz.net

SCHÜTZ
PACKAGING SYSTEMS

www.schuetz.net

Material

Inner bottle

Inner and intermediate layer:
high-molecular, high-density
polyethylene (HDPE)

Antistatic / conductive
outer layer

Additional UV and light protection
of the filling product (optional)

Optional

EVOH permeation barrier

Pallet (4-way entry)



plastic skid

Certifications

UN 31 HA1/Y (optional)

Maximum density 1.6 g/cm³

Suitable for use in ex-zones 1 and 2

Tested for electrostatic safety

Capacity

MX-EX antistatic / conductive 1000

1,000 litres (275 gal)

Filling opening

DN 150 with screw cap

DN 225 with screw cap

Outlet valves

Earthed integrated
butterfly valve DN 50

Earthed integrated
butterfly valve DN 80

Dimensions (mm)

1,200 x 1,000 x 1,160 (L x W x H)


Gewicht

MX-EX antistatic / conductive 1000

58 kg with plastic pallet

Dynamic load

Filled ECOBULK according to
the specific weight of the filling
goods



Static load

Max. 4-high

