

MX

SCHÜTZ
PACKAGING SYSTEMS

www.schuetz.net

ECOBULK Feeder

Lower costs by simplifying handling during production.



Shuttle IBC

Base IBC

- Reduction of idle times when changing containers
- Gravimetric emptying of transport containers keeps product loss at a minimum
- Production process is not interrupted
- Packaging materials are avoided
- Replaces small packaging units
- Time-effective draining of residuals

Please do not hesitate to contact us regarding any technical concerns or questions.

DESIGN

Steel frame

- Supports of special sheet metal, galvanized

Base IBC

- MX 1250

Shuttle IBC

- Exchangeable
- MX 820 or MX 1000

PALLETS (4-way entry)

steel frame



CERTIFICATIONS

UN 31 HA1/Y (optional)

CAPACITY

MX 1250

- 1,250 litres (330 gal)

FILLING OPENING (base-IBC)

- DN 150 with screw cap

OUTLET VALVES (base-IBC)

- Screwable butterfly valve DN 50
- Screwable ball valve DN 50

DIMENSIONS

Length: 1,310 mm

Width: 1,110 mm

Frame height: 1,782 mm

Height with MX 1000 stacked: 2,865 mm

WEIGHT

MX 1250: 70.0 kg

Frame: 117.0 kg

Fitting: 2.0 kg

Total: approx. 190.0 kg