

ECOBULK

MX FOODCERT & MX-EV FOODCERT

The highest standard for food safety.



Ensures compliance with all specified food standards for material, process and product:

- System certification according to FSSC 22000, (Food Safety System Certification, based on ISO 22000 in combination with ISO/TS 22002-4)
- The certification is recognised by the GFSI (Global Food Safety Initiative)
- Safety measures in accordance with HACCP
- Traceability back to batch and process level

In case of technical concerns or questions: tcs@schuetz.net

SCHÜTZ
PACKAGING SYSTEMS

www.schuetz.net

Material

Inner bottle

Extrusion blow-moulded HDPE with the EVOH permeation barrier (optional)
Antistatic outer layer (optional)
Additional UV and light protection of the filling product (optional)

Outer container

Welded tubular steel grid, galvanized

Bottom plate

To provide stability and to facilitate minimum residual contents from the inner container

Pallets (4-way entry)



Certifications

UN 31 HA1/Y (optional)

Maximum density 1.9 g/cm³

SCHÜTZ FOODCERT (optional)

System certification for food (contains materials that are FDA compliant)

Capacity

MX 640

640 litres (170 gal)

MX 820

820 litres (220 gal)

MX 1000

1,000 litres (275 gal)

MX 1250

1,250 litres (330 gal)

Filling opening

DN 150 with screw cap

DN 225 with screw cap

Outlet valves

Screwable butterfly valve DN 50

Screwable ball valve DN 50

Dimensions (mm)

MX 640

1,200 x 800 x 1,000 (L x W x H)

MX 820

1,200 x 1,000 x 1,000 (L x W x H)

MX 1000

1,200 x 1,000 x 1,160 (L x W x H)

MX 1250

1,200 x 1,000 x 1,350 (L x W x H)

Weight

MX 1000


56 kg with steel pallet

59 kg with plastic skid

59 kg with full-plastic pallet

Dynamic load

Filled ECOBULK according to the specific weight of the filling goods



Static load

Max. 4-high

