

# ECOBULK MX HV

Taking the edge out of draining viscous filling products.



- Bevelled front edges of the inner container ensure the most efficient draining of residuals
- Perfectly suited for products of high viscosity

In case of technical concerns or questions: [tcs@schuetz.net](mailto:tcs@schuetz.net)



[www.schuetz.net](http://www.schuetz.net)

## Material

### Inner bottle

Extrusion blow-moulded HDPE  
Bevelled front edges  
SMP protective barrier (optional)

### Outer container

Welded tubular steel grid, galvanized

### Bottom plate

To provide stability and to facilitate minimum residual contents from the inner container

## Pallets (4-way entry)



## Certifications

**UN 31 HA1/Y** (optional)  
Maximum density 1.9 g/cm<sup>3</sup>

**SCHÜTZ FOODCERT** (optional)  
System certification for food (contains materials that are FDA compliant)

## Capacity

**MX-HV 1000**  
1,000 litres (275 gal)

## Filling opening

DN 225 with screw cap

## Outlet valves

Integrated butterfly valve DN 80

## Dimensions (mm)

**MX-HV 1000**  
1,200 x 1,000 x 1,160 (L x W x H)

## Weight

**MX-HV 1000**  
56 kg with steel pallet  
59 kg with plastic skid  
59 kg with full-plastic pallet

## Dynamic load

Filled ECOBULK according to the specific weight of the filling goods

## Static load

Max. 4-high

